



Picture for illustration purpose only



Specifications TLWMA65BP

Electrical Specifications

Model No.	TLWMA65BP
DLC ID	PY1PNE11
Power (W) $\pm 10\%$	65 W (DLC: 66.26 W)
Input Voltage (V)	AC100-277V, 50/60Hz
Efficacy $\pm 3\%$	111.39 lm/W
Power Factor (PF)	0.9389

Photometric Specifications

CRI	72.3
CCT	4 922 K
Beam angle	$\pm 120^\circ$
Light Output $\pm 3\%$	7 380.5 lm
Dimmable	No

Mechanical Specifications

IP Rating	IP 65
Material	Die cast aluminium
Lens	PC
Product size (mm)	340 x 240 x 242.8 mm
Product size (inch)	$\pm 13\text{-}3/8 \times 9\text{-}1/2 \times 9\text{-}1/2$ in
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

Product Description:

1. Mounts on wall or optional arm.
2. A dusk-to-dawn photocell provides automatic on/off.
3. Photocell included.
4. Lightweight body material, corrosion resistant, waterproof and dustproof.
5. Save in electricity consumption compared to MH and HPS lighting fixture.
6. Warranty: 5 Years.
7. It could be fitted with sensor.

Applications:

Sentinel.

Provides general purpose area, security, roadway and landscape lighting.

Similar Products	Color	W	Lumen
TLWMA150BP	5 000 K	150 W	18 750 lm