



Shown model: SF Bracket



Picture for illustration purpose only



Specifications TLAL110TRPBK

Electrical Specifications

Model No.	TLAL110TRPBK
Power (W) $\pm 10\%$	110 W (DLC: 114.7 W)
Input Voltage (V)	AC100-277V, 50/60Hz
Efficacy	133.75 lm/W
Power Factor (PF)	0.93

Photometric Specifications

CRI	72.9
CCT	5000 K
Beam angle	130°
Light Output	15 341 lm
Dimmable	1-10V & Triac

Mechanical Specifications

IP Rating	IP66
Material	Aluminium
Lens	Clear PC
Net Weight	5.6 kg
Product size (mm)	560 x 278 x 75 mm
Product size (inch)	$\pm 22 \times 10.9 \times 2.95$ in
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

Product Description:

1. Light and slim housing.
2. Multiple bracket options. (SF, AM, TR and PM)
3. Photocell optional.
4. Easily replace traditional MH or HPS luminaire fixture.
5. Powerful light efficacy and heat dissipation design and sturdiness.
6. Save in electricity consumption compared to fluorescent lighting fixture.
7. Warranty: 5 Years.
8. It could be fitted with sensor.
9. 3000K, 4000K, 5700K, 6500K available on special request.
10. Color: Black. Other colors available on special request.

Applications:

Outdoor parking and wide area.

Similar products	Color	W	Lumen
TLAL75TRPBK	5000 K	75 W	11 079 lm
TLAL150TRPBK	5000 K	150 W	19 182 lm
TLAL180TRPBK	5000 K	180 W	22 944 lm