



### Optional accessories



## Specifications TLCDLUS4R12AWH

### Electrical Specifications

Model No.	TLCDLUS4R12AWH	
Power (W) ± 10%	5.5 W - 8 W - 12 W	
Input Voltage (V)	AC 120-347V, 50/60Hz	
Efficacy ± 3%	100 lm/W	
Power Factor (PF)	>0.9	
Dimmable	0-10V	

### Photometric Specifications

CRI	≥90	
CCT	Adjustable	
Beam angle	90°	
Light Output ± 3%	5.5W: 550 lm	8W: 800 lm
	12W: 1200 lm	

### Mechanical Specifications

IP Rating	Wet locations	
Material	Aluminum	
Lens	Frosted	
Net Weight	408 g	
Product size (mm)	± Ø151 x 109 mm	
Product size (inch)	± Ø5.94" x 4.29"	
Operating Humidity	10% - 90%	
Operating Temperature	-20°C ~ 40°C	
Lifespan (L70)	50 000 hours	

## Product Description:

- 4" recessed down light.
- 102 mm (4") hole required for installation.
- BX 24" cable with connector included.
- Adjustable CCT: 3 000 K, 3 500 K and 4 000 K using a switch.
- Adjustable power: 5.5 W, 8 W et 12 W using a switch.
- Ultra thin 4" recessed down light.
- Color: white.  
Possibility to customize colors using optional accessories.

## Applications:

Shopping centers, residential buildings, hotels, schools, houses, etc.

[info@technilight.ca](mailto:info@technilight.ca)

[WWW.TECHNILIGHT.CA](http://WWW.TECHNILIGHT.CA)