



### Optional accessories



## Specifications TLCDLUS6R17AWH

### Electrical Specifications

Model No.	TLCDLUS6R17AWH	
Power (W) ± 10%	7 W - 10 W - 17 W	
Input Voltage (V)	AC 120-347V, 50/60Hz	
Efficacy ± 3%	100 lm/W	
Power Factor (PF)	>0.9	
Dimmable	0-10V	

### Photometric Specifications

CRI	≥90	
CCT	Adjustable	
Beam angle	90°	
Light Output ± 3%	7W: 700 lm	10W: 1000 lm
	17W: 1700 lm	

### Photometric Specifications

IP Rating	Wet locations
Material	Aluminum
Lens	Frosted
Net weight	598 g
Product size (mm)	± Ø203.2 x 127 mm
Product size (inch)	± Ø8.27" x 5.13"
Operating Humidity	10% - 90%
Operating Temperature	-20°C ~ 40°C
Lifespan (L70)	50 000 hours

## Product Description:

- 6" recessed down light.
- 159 mm (6 1/4") hole required for installation.
- BX 24" cable with connector included.
- Adjustable CCT: 3 000 K, 3 500 K and 4 000 K using a switch.
- Adjustable power: 7 W, 10 W et 17 W using a switch.
- Ultra thin 4" recessed down light.
- Color: white.  
Possibility to customize colors using optional accessories.

## Applications:

Shopping centers, residential buildings, hotels, schools, houses, etc.