


TLDL80N

IP65

Fixing aluminium plate available. Not included.



J15645A



Specifications

TLDL80N

Electrical Specifications				
TLDL80N				
80 W (DLC: 80.38 W)				
AC100-277V, 50/60Hz				
126.64 lm/W				
0.9056				

Photometric Specifications			
CRI	73		
CCT	4000 K		
Beam angle	105°		
Light Output	10 179 lm		
Dimmable	1-10V & Triac		

Mechanical Specifications				
IP Rating	IP65			
Material	Die cast aluminium			
Lens	Clear Flat PC			
Net Weight	11.6 kg			
Product size (mm)	355.6 x 355.6 x 127 mm			
Product size (inch)	± 14 x 14 x 5 in			
Operating Humidity	10% - 90%			
Operating Temperature	-35°C ~ 45°C			



Product Description:

- 1. Die cast aluminium housing for rugged mounting and heat dissipation.
- 2. Surface mount with quick installation kits and an aluminium plate.
- 3. No toxic chemicals/ROHS compliant.
- 4. Save up in electricity consumption compared to fluorescent lighting fixture.
- 5. Warranty: 5 Years.
- 6. It could be fitted with sensor.
- 7. 2700K and 5700K available on special request.
- 8. Color: white.

Applications:

Gas stations, workshops, warehouses, factories, markets, etc.

Designed for wet locations. Indoor and outdoor.

Similar product	Color	W	Lumen
TLDL40N	4000 K	40 W	5 530 lm

info@technilight.ca