



Pictures for illustration purpose only



## Specifications TLFL120HPMPBK

### Electrical Specifications

Model No.	TLFL120HPMPBK
Power (W) $\pm$ 10%	120 W (DLC: 114.1 W)
Input Voltage (V)	AC 347/480V, 50/60Hz
Efficacy	133.17 lm/W
Power Factor (PF)	0.9046

### Photometric Specifications

CRI	74.1
CCT	5 000 K
Beam angle	120 °
Light Output	15 195 lm
Dimmable	1-10V

### Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Clear (Tempered glass)
Net Weight	6.6 kg
Product size (mm)	380 x 270 x 90 mm
Product size (inch)	$\pm$ 15 x 10-5/8 x 3-1/2 in
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

## Product Description:

1. Mounting option: PM
2. Various mounting options available. (TU, SF, PM)
3. Clear, flat tempered glass lens, water-resistant.
4. Save on electricity consumption compared to fluorescent lighting fixture.
5. Color: black.  
Other colors available on special request.
6. Warranty: 5 Years.
7. It could be fitted with sensor.
8. 3 000 K, 4 000 K available on special request.

## Applications:

Designed for use in wet locations.  
Flood luminaire.

Similar products	Color	W	Lumen
TLFL120PMPBK	5 000 K	120 W	16 882 lm
TLFL200PMPBK	5 000 K	200 W	28 314 lm
TLFL200HPMPBK	5 000 K	200 W	27 198 lm