



Pictures for illustration purpose only.



## Specifications TLFL120PMPBK

### Electrical Specifications

Model No.	TLFL120PMPBK
Power (W) $\pm 10\%$	120 W (DLC: 120.7 W)
Input Voltage (V)	AC 100/277V, 50/60Hz
Efficacy	139.87 lm/W
Power Factor (PF)	0.9009

### Photometric Specifications

CRI	74.7
CCT	5 000 K
Beam angle	120 °
Light Output	16 882 lm
Dimmable	1-10V

### Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Clear (Tempered glass)
Net Weight	6 kg
Product size (mm)	380 x 270 x 90 mm
Product size (inch)	$\pm 15 \times 10\text{-}5/8 \times 3\text{-}1/2$ in
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

## Product Description:

1. Mounting option: PM (Pole Mount)
2. Various mounting options available. (TU, SF, PM)
3. Clear, flat tempered glass lens, water-resistant.
4. Save on electricity consumption compared to fluorescent lighting fixture.
5. Color: black.  
Other colors available on special request.
6. Warranty: 5 Years.
7. It could be fitted with sensor.
8. 3 000 K, 4 000 K available on special request.

## Applications:

Designed for use in wet locations.  
Flood luminaire.

Similar products	Color	W	Lumen
TLFL50SWPBK	5 000 K	50 W	6 552.2 lm
TLFL75SWPBK	5 000 K	75 W	10 832 lm
TLFL200PMPBK	5 000 K	200 W	28 341 lm