



Pictures for illustration purpose only



Specifications TLFL200HPMPBK

Electrical Specifications

Model No.	TLFL200HPMPBK
Power (W) $\pm 10\%$	200 W (DLC: 204.7 W)
Input Voltage (V)	AC 347/480V, 50/60Hz
Efficacy	132.87 lm/W
Power Factor (PF)	0.951

Photometric Specifications

CRI	74.1
CCT	5 000 K
Beam angle	120 °
Light Output	27 198 lm
Dimmable	1-10V

Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Clear (Tempered glass)
Net Weight	10.2 kg
Product size (mm)	500 x 335 x 100 mm
Product size (inch)	$\pm 20 \times 13 \times 4$ po
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

Product Description:

1. Mounting option: PM
2. Various mounting options available.
(TU, SF, PM)
3. Clear, flat tempered glass lens, water-resistant.
4. Save on electricity consumption compared to fluorescent lighting fixture.
5. Color: black.
Other colors available on special request.
6. Warranty: 5 Years.
7. It could be fitted with sensor.
8. 3 000 K, 4 000 K available on special request.

Applications:

Designed for use in wet locations.
Flood luminaire.

Similar products	Color	W	Lumen
TLFL120PMPBK	5 000 K	120 W	16 882 lm
TLFL200PMPBK	5 000 K	200 W	28 314 lm
TLFL120HPMPBK	5 000 K	120 W	15 195 lm