



Pictures for illustration purpose only.



Specifications TLFL200MPBK

Electrical Specifications

Model No.	TLFL200MPBK
Power (W) $\pm 10\%$	200 W (DLC: 204.5 W)
Input Voltage (V)	AC 100/277V, 50/60Hz
Efficacy	138.59 lm/W
Power Factor (PF)	0.9129

Photometric Specifications

CRI	74.7
CCT	5 000 K
Beam angle	120 °
Light Output	28 341 lm
Dimmable	1-10V

Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Clear (Tempered glass)
Net Weight	10.6 kg
Product size (mm)	500 x 335 x 100 mm
Product size (inch)	$\pm 20 \times 13 \times 4$ in
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

Product Description:

1. Mounting option: PM (Pole Mount)
2. Various mounting options available. (TU, SF, PM)
3. Clear, flat tempered glass lens, water-resistant.
4. Save on electricity consumption compared to fluorescent lighting fixture.
5. Color: black.
Other colors available on special request.
6. Warranty: 5 Years.
7. It could be fitted with sensor.
8. 3 000 K, 4 000 K available on special request.

Applications:

Designed for use in wet locations.
Flood luminaire.

Similar products	Color	W	Lumen
TLFL50SFPBK	5 000 K	50 W	6 552.2 lm
TLFL75SFPBK	5 000 K	75 W	10 832 lm
TLFL120MPBK	5 000 K	120 W	16 882 lm