




Picture for illustration purpose only



Specifications TLFL280TUPBK

Electrical Specifications

Model No.	TLFL280TUPBK
Power (W) $\pm 10\%$	280 W (DLC: 291.7 W)
Input Voltage (V)	AC100-277V, 50/60Hz
Efficacy	148.31 lm/W
Power Factor (PF)	0.93

Photometric Specifications

CRI	76.3
CCT	5 000 K
Beam angle	111.9°
Light Output	43 261 lm
Dimmable	1-10V

Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Clear (Tempered glass)
Net Weight	18 kg
Product size (mm)	657 x 410 x 195.9 mm
Product size (inch)	$\pm 25\text{-}7/8 \times 16\text{-}1/8 \times 7\text{-}3/4$
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

Product Description:

1. Mounting option: TU (Big Trunnion).
2. Various mounting options available. (TU, SF, PM and TR)
3. Photocell optional.
4. Clear, flat tempered glass lens, water-resistant.
5. Save on electricity consumption compared to fluorescent lighting fixture.
6. Color: black.
Other colors available on special request.
7. Warranty: 5 Years.
8. It could be fitted with sensor.
9. 3 000 K, 4 000 K available on special request.

Applications:

Designed for use in wet locations.
Architectural flood luminaire.

Similar products	Color	W	Lumen
TLFL280HTUPBK	5 000 K	280 W	42 015 lm
TLFL280SFPBK	5 000 K	280 W	43 261 lm
TLFL320TRPBK	5 000 K	320 W	43 386 lm