



Pictures for illustration purpose only



Specifications TLFL75SFPBK

Electrical Specifications

Model No.	TLFL75SFPBK
Power (W) $\pm 10\%$	75 W (DLC: 76.79 W)
Input Voltage (V)	AC 100/277V, 50/60Hz
Efficacy	141.06 lm/W
Power Factor (PF)	0.9137

Photometric Specifications

CRI	73
CCT	5 000 K
Beam angle	120°
Light Output	10 832 lm
Dimmable	1-10V

Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Clear (Tempered glass)
Net Weight	5.3 kg
Product size (mm)	312.3 x 172.3 x 97.8 mm
Product size (inch)	$\pm 13 \times 6\text{-}3/4 \times 3\text{-}3/4$ in
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

Product Description:

1. Mounting option: SF (Slip Fitter)
2. Various mounting options available. (TU, SF, SW)
3. Clear, flat tempered glass lens, water-resistant.
4. Save on electricity consumption compared to fluorescent lighting fixture.
5. Color: black.
Other colors available on special request.
6. Warranty: 5 Years.
7. It could be fitted with sensor.
8. 3 000 K, 4 000 K available on special request.

Applications:

Designed for use in wet locations.
Flood luminaire.

Similar products	Color	W	Lumen
TLFL50SFPBK	5 000 K	50 W	6 552.2 lm
TLFL120SFPBK	5 000 K	120 W	16 882 lm
TLFL200SFPBK	5 000 K	200 W	28 341 lm

info@technilight.ca

WWW.TECHNILIGHT.CA