



Pictures for illustration purpose only



Specifications TLFLF50SWPBK

Electrical Specifications

Model No.	TLFLF50SWPBK
DLC ID	PLYISGZZO6XE
Power (W) $\pm 10\%$	50 W
Input Voltage (V)	AC 120/277V, 50/60Hz
Efficacy $\pm 3\%$	120 lm/W
Power Factor (PF)	0.8793
Total harmonic distortion	11.82%

Photometric Specifications

CRI	71.2
CCT	5 000 K
Beam angle	80° x 110°
Light Output $\pm 3\%$	6 000 lm
Dimmable	No

Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminum
Lens	Polycarbonate
Net Weight	2.5 kg
Product size (mm)	$\pm 228 \times 203 \times 50$ mm
Product size (inch)	$\pm 9 \times 8.4 \times 2.3$ in
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 45°C
Lifespan (L70)	72 000 hours

Product Description:

1. Mounting option: SW ("Knuckle" bracket) NPT 1/2 in.
2. 2 mounting options available. (SW and TU)
3. Built with materials that have little expansion at the temperature. Stay waterproof to -40°C.
4. Save on electricity consumption compared to standard lighting fixture.
5. Color: black.
6. Warranty: 5 Years.
7. 18" power cord.

Applications:

Designed for use in wet locations.
Flood luminaire.

Similar products	Color	W	Lumen
TLFLF15SWPBK	5 000 K	15 W	1 800 lm
TLFLF30SWPBK	5 000 K	50 W	3 600 lm
TLFLF100SWPBK	5 000 K	100 W	13 550 lm

info@technilight.ca

WWW.TECHNILIGHT.CA