



Pictures for illustration purpose only



Specifications TLHB200120P

Electrical Specifications

Model No.	TLHB200120P
Power (W) $\pm 10\%$	200 W
Input Voltage (V)	100-277 V, 50/60 Hz
Efficacy	145 lm/W
Power Factor (PF)	0.9

Photometric Specifications

CRI	80
CCT	5 000 K
Beam angle	120°
Light Output	29 000 lm
Dimmable	0-10V

Mechanical Specifications

IP Rating	IP65
Material	Aluminum
Lens	Clear (Polycarbonate)
Net Weight	5.7 kg
Product size (mm)	Ø 400 x 141 mm
Product size (inch)	± Ø15 3/4 x 5 1/2 in
Operating Temperature	-35°C ~ 50°C

Product Description:

1. Lightweight lamp body for easier installation in high ceiling areas.
2. Polycarbonate lens with 120° projection.
3. 500 mm stainless steel suspension kit included.
4. 2 meters power cable.
5. 3 000 K, 4 000 K and frost lens available on special request.
6. Over 70% energy saving compared to conventional lights.
7. Resistance to impact.
8. Aluminum heat sink for maximum thermal conductivity to ensure extended lifetime.

Applications:

Warehouse, workshop, garage, industry, arena and other high ceiling areas.

Similar products	Color	W	Lumen
TLHB100120P	5 000 K	100 W	14 500 lm
TLHB150120P	5 000 K	150 W	21 750 lm
TLHB240120P	5 000 K	240 W	34 800 lm

info@technilight.ca

WWW.TECHNILIGHT.CA