TLHBM4C100V1P

Picture for illustration purpose only

Specifications TLHBM4C100V1P

Electrical Specifications	
Model No.	TLHBM4C100V1P
Power (W) ± 10%	100 W (DLC: 92 W)
Input Voltage (V)	AC100-240/277V, 50/60Hz
Efficacy	137.35 lm/W
Power Factor (PF)	0.95

Photometric Specifications	
CRI	84.6
CCT	5000 K
Beam angle	120°
Light Output	12 647 lm
Dimmable	1-10V

Mechanical Specifications	
IP Rating	IP20
Material	Aluminium
Lens	Diffuser PC
Net Weight	7 kg
Product size (mm)	1090 x 322 x 59 mm
Product size (inch)	± 43 x 12-5/8 x 2-1/4
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

Product Description:

1. LED luminaire for high ceiling.
2. This lighting system is deal for replacing conventional HID or fluorescent high bay systems.
3. High performing lightweight aluminium heat sink.
4. Save up to 60% in electricity consumption compared to fluorescent lighting fixture.
5. Stainless steel suspension kit 1 333mm.
6. Warranty: 5 Years.
7. It could be fitted with sensor.
8. 4000K available on special request.
9. Color: white. Other colors available on special request.

Applications:

Warehouse, workshop, factory, garage, gymnasium, exhibition areas and others.

Similar products	Color	W	Lumen
TLHBM4C100V2P	5000 K	100 W	13 045 lm
TLHBM4C150V1P	5000 K	150 W	19 883 lm
TLHBM4C200V1P	5000 K	200 W	26 660 lm

info@technilight.ca