



Specifications TLHBNU150PS

Electrical Specifications

Model No.	TLHBNU150PS
DLC ID	PLG7G4N0BE03
Power (W) $\pm 10\%$	150 W
Input Voltage (V)	AC120-347V, 50/60Hz
Efficacy $\pm 3\%$	146 lm/W
Power Factor (PF)	0.9
Total Harmonic Distorsion	$\leq 15\%$

Photometric Specifications

CRI	≥ 80
CCT	5 000 K
Beam angle	115°
Light Output $\pm 3\%$	21 900 lm
Dimmable	0-10V

Mechanical Specifications

IP Rating	IP66 / IP69K
Material	Aluminum
Lens	Clear (Tempered glass)
Net Weight	5.75 kg
Product size (mm)	Ø434 x 192 mm
Product size (inch)	$\pm \text{Ø}17 \times 7\text{-}1/2$ in
Operating Temperature	-40°C ~ 45°C
Lifespan (L70)	60 000 hours



Remote control
setting for
motion sensor
(optional)




Product Description:

- Lightweight lamp body for easier installation in high ceiling areas. With epoxy paint, resistant to corrosion.
- Acid and alkaline resistant tempered glass lens.
- Built-in motion sensor. Remote control optional.
- 3/4" NPT mounting with hook included.
- Each lamp are with 2 m power cable.
- 3 000 K, 4 000 K and 5 700 K available on special request.
- Over 70% energy savings compared to conventional lights with similar lumen output.
- Resistance to impact.
- NSF certified for use in the food industry.

Applications:

Food processing space, pharmaceutical factory, supermarket, farm, car wash, etc.

Installation with NPT 3/4" pipe



info@technilight.ca

WWW.TECHNILIGHT.CA