



Accessories included



Specifications TLHPA4C150V1P

Electrical Specifications

Model No.	TLHPA4C150V1P
DLC ID	S-QRKZ5M
Power (W) $\pm 10\%$	150 W (DLC: 141.1 W)
Input Voltage (V)	AC100/277V, 50/60Hz
Efficacy $\pm 3\%$	144.68 lm/W
Power Factor (PF)	0.906

Photometric Specifications

CRI	85
CCT	5 000 K
Beam angle	120°
Light Output $\pm 3\%$	20 414 lm
Dimmable	1-10V

Mechanical Specifications

IP Rating	IP65
Material	Polycarbonate
Lens	Clear (Reflector:MCPCB)
Net Weight	12 kg
Product size (mm)	1265 x 240 x 150 mm
Product size (inch)	$\pm 49\text{-}3/4 \times 9\text{-}1/2 \times 5\text{-}7/8$
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C
Lifespan (L70)	54 000 hours



Product Description:

- Lightweight body material, corrosion resistant, waterproof and dustproof.
- Replaces any conventional high-bay fixture. Installation: Ceiling, wall or suspension.
- Perfect replacement for the whole set of T8 and T5 fluorescent lighting fixture.
- Save up to 60% in electricity consumption compared to fluorescent lighting fixture.
- Body and diffuser could meet the IK08 test requirement.
- Warranty: 5 Years.
- It could be fitted with sensor.
- 3 000 K, 4 000 K available on special request.
- Frosted lens available.
- Polycarbonate fasteners and suspension kit included.

Applications:

Suitable for farm, food processing sector, warehouse, wet locations etc.

info@technilight.ca

WWW.TECHNILIGHT.CA