



Pictures for illustration purpose only.



Specifications TLPBLUS14W35AD

Electrical Specifications

Model No.	TLPBLUS14W35AD
DLC ID	PL2AAM7LK39Z
Power (W) tunable	20W - 25W - 30W - 35W
Input Voltage (V)	AC100-347V, 50/60Hz
Efficacy ± 3%	123.31 lm/W
Power Factor (PF)	0.9018
Total Harmonic Distortion	≤15 %

Photometric Specifications

CRI	81.1
CCT tunable	3000K - 3500K - 4000K - 5000K
Beam Angle	120°
Light Output ± 3%	4 218.3 lm
Dimmable	0-10 V

Mechanical Specifications

IP Rating	IP40
Material	Aluminum
Lens	Frosted PC
Net Weight	2.5 kg
Product size (mm)	300 x 1213 x 30 mm
Product size (in)	± 12 x 48 x 1.2 in
Operating Humidity	10% - 90%
Operating Temperature	-20°C ~ 50°C
Lifespan (L70)	60 000 hours

Product Description:

1. Backlight LED panel luminaire.
2. Tunable power and CCT with a switch.
3. Installation: suspended / suspended ceiling / surface mount with optional mounting frame.
4. "IC" type
5. 0-10 V variable intensity and compatible with all 0-10 V dimmer models.
6. Perfect replacement for the whole set of T8 and T5 fluorescent lighting fixture.
7. Uniform brightness, high performance, low energy consumption and low radiant heat.
8. Warranty: 5 Years.

Applications:

Office, business place, clinic, airport, commerce, hotel, basement, etc.

Similar products	Color	W	Lumen
TLPBLUS22W35D	3000K to 5000K	20W to 35W	4 550 lm
TLPBLUS24W50D	3000K to 5000K	35W to 50W	6 500 lm

info@technilight.ca

WWW.TECHNILIGHT.CA