



Picture for illustration purpose only



## Specifications TLPL14W36ND

### Electrical Specifications

Model No.	TLPL14W36ND
Power (W) $\pm 10\%$	36 W
Input Voltage (V)	AC100-277, 50/60Hz
Efficacy	97.78 lm/W

### Photometric Specifications

CRI	83
CCT	4000 K
Light Output	3274 lm
Dimmable	1-10V & PWM

### Mechanical Specifications

Product size (mm)	300 x 1213
Product size (ft)	1 x 4

Similar products	Color	W	Lumen
TLPL14W45PD	5000 K	45 W	4 281 lm
TLPL14W40HPD (347V)	5000 K	40 W	4 086 lm
TLPL14W40HND (347V)	4000 K	40 W	3920.9 lm

## Product Description:

1. LED luminaire with translucent diffuser and several installation options.
2. Installation: suspended / ceiling, recessed / surface mount.
3. Available with variable intensity and can be used for commercial and advertising lighting as well as for functional or ambient lighting systems.
4. Perfect replacement for the whole set of T8 and T5 fluorescent lighting fixture.
5. 9 mm panel. Edge-lit luminaire.
6. Brightness of the LED panel is very efficient, low energy consumption and low radiant heat.
7. 3000K, 4000K available on special request.
8. Frame color: white. Other colors available on special request.
9. Warranty: 5 Years.

## Applications:

Office, super market, business place, clinic, airport, commerce, hall, hotel, etc.