



Picture for illustration purpose only



## Specifications TLPL22W45ND

### Electrical Specifications

Model No.	TLPL22W45ND
Power (W) $\pm 10\%$	45 W
Input Voltage (V)	AC100-277V, 50/60Hz
Efficacy	99.87 lm/W

### Photometric Specifications

CRI	82
CCT	4000 K
Light Output	4466 lm
Dimmable	1-10V & PWM

### Mechanical Specifications

Product size (mm)	603 x 603
Product size (ft)	2 x 2

Similar products	Color	W	Lumen
TLPL22W40HPD (347V)	5000 K	40 W	5700 lm
TLPL22W40HND (347V)	4000 K	40 W	5600 lm
TLPL24W60PD	5000 K	60 W	5568 lm

## Product Description:

1. LED luminaire with translucent diffuser and several installation options.
2. Installation: suspended / ceiling, recessed / surface mount.
3. Available with variable intensity and can be used for commercial and advertising lighting as well as for functional or ambient lighting systems.
4. Perfect replacement for the whole set of T8 and T5 fluorescent lighting fixture.
5. 9 mm panel. Edge-lit luminaire.
6. Brightness of the LED panel is very efficient, low energy consumption and low radiant heat.
7. 3000K, 4000K available on special request.
8. Frame color: white. Other colors available on special request.
9. Warranty: 5 Years.

## Applications:

Office, super market, business place, clinic, airport, commerce, hall, hotel, etc.