



Picture for illustration purpose only



## Specifications TLPL24W72HPD

### Electrical Specifications

Model No.	TLPL24W72HPD
Power (W) $\pm 10\%$	72 W
Input Voltage (V)	AC277-347V, 50/60Hz
Efficacy	144 lm/W
Power Factor (PF)	0.9

### Photometric Specifications

CRI	80
CCT	5000 K
Light Output	10 360 lm
Dimmable	1-10V & PWM

### Mechanical Specifications

Product size (mm)	603 x 1213
Product size (ft)	2 x 4

Similar Product	Color	W	Lumen
TLPL24W60PD	5000 K	60 W	5 568 lm
TLPL24W72PD	5000 K	72 W	6 680 lm
TLPL24W72HND (347V)	4000 K	72 W	10 220 lm

## Product Description:

1. LED luminaire with translucent diffuser and several installation options.
2. Installation: suspended / ceiling, recessed / surface mount.
3. Available with variable intensity and can be used for commercial and advertising lighting as well as for functional or ambient lighting systems.
4. Perfect replacement for the whole set of T8 and T5 fluorescent lighting fixture.
5. 9 mm panel. Edge-lit luminaire.
6. Brightness of the LED panel is very efficient, low energy consumption and low radiant heat.
7. 3000K, 5000K available on special request.
8. Frame color: white. Other colors available on special request.
9. Warranty: 5 Years.

## Applications:

Office, super market, business place, clinic, airport, commerce, hall, hotel, etc.