



Picture for illustration purpose only



Specifications TLPL24W72ND

Electrical Specifications

Model No.	TLPL24W72ND
Power (W) $\pm 10\%$	72 W
Input Voltage (V)	AC100-277V, 50/60Hz
Efficacy	91.17 lm/W

Photometric Specifications

CRI	82
CCT	4000 K
Light Output	6420 lm
Dimmable	1-10V & PWM

Mechanical Specifications

Product size (mm)	603 x 1213
Product size (ft)	2 x 4

Similar products	Color	W	Lumen
TLPL24W72PD	5000 K	72 W	6 680 lm
TLPL24W72HPD (347V)	5000 K	72 W	10 360 lm
TLPL24W72HND (347V)	4000 K	72 W	10 220 lm

Product Description:

1. LED luminaire with translucent diffuser and several installation options.
2. Installation: suspended / ceiling, recessed / surface mount.
3. Available with variable intensity and can be used for commercial and advertising lighting as well as for functional or ambient lighting systems.
4. Perfect replacement for the whole set of T8 and T5 fluorescent lighting fixture.
5. 9 mm panel. Edge-lit luminaire.
6. Brightness of the LED panel is very efficient, low energy consumption and low radiant heat.
7. 3000K, 4000K available on special request.
8. Frame color: white. Other colors available on special request.
9. Warranty: 5 Years.

Applications:

Office, super market, business place, clinic, airport, commerce, hall, hotel, etc.