



## Specifications TLT5B4F24P

### Electrical Specifications

Model No.	TLT5B4F24P
DLC ID	PL03DHN4HTWJ
Power (W) $\pm 10\%$	24 W
Input Voltage (V)	AC120-277V, 50/60Hz
Efficacy $\pm 3\%$	188.64 lm/W
Power Factor (PF)	0.9
Total harmonic distortion	15%

### Photometric Specifications

CRI	80
CCT	5 000 K
Beam angle	140°
Light Output $\pm 3\%$	4 514.2 lm
Dimmable	No

### Mechanical Specifications

Material	Aluminum + PC
Lens	Frosted
Product size (mm)	1162 x 23 mm
Product size (inch)	$\pm 48 \times 7/8$ inch
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 40°C
Lifespan (L70)	>50 000 hours

## Product Description:

1. Compatible with enclosed luminaire.
2. Perfect replacement for the whole set of T5 fluorescent lighting fixture.
3. Soft and uniform light. No glare and no flickering.
4. Approximately 50% economy on electricity consumption compared to fluorescent lighting fixture.
5. "Type B". Direct supply, double-ended, 120 to 277 VAC.
6. Warranty: 5 Years.
7. 4 000 K available.

## Applications:

Fluorescent T5 tubes replacement.



[info@technilight.ca](mailto:info@technilight.ca)

**WWW.TECHNILIGHT.CA**