



## Specifications TLTFUS22W40AD

### Electrical specifications

Model No.	TLTFUS22W40AD
DLC ID	S-RNPXVC
Adjustable power (W) ± 10%	20W - 30W - 40W
Input Voltage (V)	AC 120/347V, 50/60Hz
Efficacy ± 3%	127.55 lm/W
Power Factor (PF)	0.951
Surge protection	N/D
Total harmonic distortion	13.2 %

### Photometric specifications

CRI	84
Adjustable CCT	3500K / 4000K / 5000K
Beam angle	120°
Light Output ± 3%	20W: 2500 lm    30W: 3750 lm 40W: 4833 lm
Dimmable	0-10V

### Mechanical specifications

IP Rating	IP20
Material	SPCC + PC
Lens	Frosted
Net Weight	5.2 kg
Product size (mm)	± 603 x 603 x 50 mm
Product size (inch)	± 24 x 24 x 2 in
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 50°C
Lifespan (L70)	54 000 hours

## Product description:

- Large supply voltage range 120-347V.
- Adjustable CCT: 3500K / 4000K / 5000K.
- Adjustable power: 20W / 30W / 40W.
- Versatile design makes installation easy which reduces installation time and costs.
- Save on electricity consumption compared to fluorescent lighting fixture.
- Warranty: 5 years.
- High efficiency reflective PC cover, soft and bright lighting.

## Applications:

Suitable for metros, conference rooms, shops, supermarkets, etc.