



Specifications TLTFUS24W50AD

Electrical specifications

Model No.	TLTFUS24W50AD
DLC ID	S-W7U69D
Adjustable power (W) ± 10%	30W - 40W - 50W
Input Voltage (V)	AC 120/347V, 50/60Hz
Efficacy ± 3%	126.26 lm/W
Power Factor (PF)	0.952
Surge protection	N/D
Total harmonic distortion	12.6 %

Photometric specifications

CRI	82
Adjustable CCT	3500K / 4000K / 5000K
Beam angle	120°
Light Output ± 3%	30W: 3750 lm 40W: 5000 lm 50W: 5791 lm
Dimmable	0-10V

Mechanical specifications

IP Rating	IP20
Material	SPCC + PC
Lens	Frosted
Net Weight	7 kg
Product size (mm)	± 1213 x 603 x 50 mm
Product size (inch)	± 48 x 24 x 2 in
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 50°C
Lifespan (L70)	54 000 hours

Product description:

- Large supply voltage range 120-347V.
- Adjustable CCT: 3500K / 4000K / 5000K.
- Adjustable power: 30W / 40W / 50W.
- Versatile design makes installation easy which reduces installation time and costs.
- Save on electricity consumption compared to fluorescent lighting fixture.
- Warranty: 5 years.
- High efficiency reflective PC cover, soft and bright lighting.

Applications:

Suitable for metros, conference rooms, shops, supermarkets, etc.