



Pictures for illustration purpose only



Specifications TLUTD4R9ABK

Electrical Specifications

Model No.	TLUTD4R9ABK
Power (W) $\pm 10\%$	9 W
Input Voltage (V)	AC120 V, 60Hz
Efficacy $\pm 3\%$	75 lm/W
Power Factor (PF)	>0.9
Dimmable	0-10V

Photometric Specifications

CRI	>80
CCT	Adjustable
Beam angle	120°
Light Output $\pm 3\%$	650 lm

Mechanical Specifications

IP Rating	IP20
Material	Aluminum + Metal box
Lens	Frosted (Polycarbonate)
Net Weight	Box: 175g Luminaire: 130g
Product size (mm)	$\pm \varnothing 123 \times 32$ mm
Product size (inch)	$\pm \varnothing 4.84 \times 1.26$ in
Operating Humidity	10% - 90%
Operating Temperature	-30°C ~ 45°C
Lifespan (L70)	50 000 hours

Product Description:

1. Ultra thin 4" recessed down light.
2. Type IC.
3. Airtight according to ASTM E283-04.
4. Junction box with quick connector included.
5. 5 CCT: adjustable 2 700 K, 3 000 K, 3 500 K, 4 000 K et 5 000 K using a switch.
6. No toxic chemicals, RoHS compliant.
7. Color: black.

Applications:

Houses, schools, shopping centers, etc.



info@technilight.ca

WWW.TECHNILIGHT.CA