



Picture for illustration purpose only



Specifications TLVP4C30DD

Electrical Specifications

Model No.	TLVP4C30DD
Power (W) $\pm 10\%$	30 W (DLC: 30.9 W)
Input Voltage (V)	AC100-277V, 50/60Hz
Efficacy	125.1 lm/W
Power Factor (PF)	0.9214

Photometric Specifications

CRI	80
CCT	2 700 K
Beam angle	120°
Light Output	3 866 lm
Dimmable	0-10V or triac

Mechanical Specifications

IP Rating	IP66
Material	Polycarbonate
Lens	Clear
Net Weight	2.1 kg
Product size (mm)	1 160 x 120 x 108 mm
Product size (inch)	$\pm 45\text{-}5/8 \times 4\text{-}11/16 \times 4\text{-}1/4$
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

Product Description:

1. Lightweight body material, corrosion resistant, waterproof and dustproof.
2. Easy Installation with fast connection design, shorten the installation process and save labor cost.
3. Perfect replacement for the whole set of T8 and T5 fluorescent lighting fixture.
4. Save up to 60% in electricity consumption compared to fluorescent lighting fixture.
5. Body and diffuser could meet the IK08 test requirement.
6. Warranty: 5 Years.
7. It could be fitted with sensor.
8. 3 000 K, 4 000 K, 5 700 K available on special request.
9. Frosted lens available.
10. Polycarbonate fasteners included.

Applications:

Suitable for farm, food processing sector, warehouse, wet locations etc.

Similar products	Color	W	Lumen
TLVP4C30PD	5 000 K	30 W	4 527 lm
TLVP4C48PD	5 000 K	48 W	6 157.2 lm
TLVP5C75PD	5 000 K	75 W	9 705.8 lm