



Specifications TLVP4F30PD

Electrical Specifications

Model No.	TLVP4F30PD
DLC ID	PL5QMGRW6VAD
Power (W) $\pm 10\%$	30 W (DLC 30.4 W)
Input Voltage	AC120-277V, 50/60Hz
Efficacy $\pm 3\%$	129.34 lm/W
Power Factor	0.919
Total harmonic distortion	12.5%

Photometric Specifications

CRI	85
CCT	5 000 K
Beam angle	120°
Light Output $\pm 3\%$	3 937 lm
Dimmable	0-10V or triac

Mechanical Specifications

IP Rating	IP66 / NEMA 4X
Material	Polycarbonate
Lens	Frosted
Net Weight	2.1 kg
Product size (mm)	1 160 x 120 x 108 mm
Product size (inch)	$\pm 45\text{-}5/8 \times 4\text{-}11/16 \times 4\text{-}1/4$ "
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C
Lifespan (L70)	54 000 hours

Product Description:

- Lightweight body material, corrosion resistant, waterproof and dustproof.
- Easy Installation with fast connection design, shorten the installation process and save labor cost.
- Perfect replacement for the whole set of T8 and T5 fluorescent lighting fixture.
- Save up to 60% in electricity consumption compared to fluorescent lighting fixture.
- Body and diffuser could meet the IK08 test requirement.
- Warranty: 5 Years.
- It could be fitted with sensor.
- Other CCT available on special request.
- Clear lens available separately.
- Polycarbonate fasteners included.

Applications:

Suitable for farm, food processing sector, warehouse, wet locations etc.

info@technilight.ca

WWW.TECHNILIGHT.CA