



Picture for illustration purpose only



Specifications TLWM40PBK

Electrical Specifications

Model No.	TLWM40PBK
Power (W) $\pm 10\%$	40 W (DLC: 39.83 W)
Input Voltage (V)	AC100/277V, 50/60Hz
Efficacy	120.01 lm/W
Power Factor (PF)	0.92

Photometric Specifications

CRI	73.8
CCT	5000 K
Beam angle	103.8°
Light Output	4 780 lm
Dimmable	0-10V

Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Clear
Net Weight	14.5 kg
Product size (mm)	462 x 230 x 240 mm
Product size (inch)	$\pm 18\text{-}1/4 \times 9\text{-}1/8 \times \text{-}9\text{-}1/2$ po
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

Product Description:

1. DLC 4.0 Standard.
2. Die cast aluminum housing provides solid mounting to wall.
3. Photocell optional.
4. Save on electricity consumption compared to fluorescent lighting fixture.
5. Color: black.
Other colors available on special request.
6. Warranty: 5 Years.
7. It could be fitted with sensor.

Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.

Similar products	Color	W	Lumen
TLWM90HPBK	5000 K	90 W	11 531 lm
TLWME100PBK	5000 K	100 W	12 122 lm
TLWME140PBK	5000 K	140 W	17 149 lm