



Picture for illustration purpose only



Specifications TLWMA65BP

Electrical Specifications

Model No.	TLWMA65BP
Power (W) ± 10%	65 W (DLC: 66.26 W)
Input Voltage (V)	AC100-277V, 50/60Hz
Efficacy	111.39 lm/W
Power Factor (PF)	0.9389

Photometric Specifications

CRI	72.3
CCT	4 922 K
Beam angle	±120°
Light Output	7 380.5 lm
Dimmable	No

Mechanical Specifications

IP Rating	IP 65
Material	Die cast aluminium
Lens	PC
Product size (mm)	340 x 240 x 242.8 mm
Product size (inch)	± 13-3/8 x 9-1/2 x 9-1/2 in
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

Product Description:

1. Mounts on wall or optional arm.
2. A dusk-to-dawn photocell provides automatic on/off.
3. Photocell included.
4. Lightweight body material, corrosion resistant, waterproof and dustproof.
5. Save in electricity consumption compared to MH and HPS lighting fixture.
6. Warranty: 5 Years.
7. It could be fitted with sensor.

Applications:

Sentinel.

Provides general purpose area, security, roadway and landscape lighting.

Similar products	Color	W	Lumen
TLHSC100P	5000 K	100 W	11 984 lm
TLHSF100P	5000K	100 W	10 870 lm