



Picture for illustration purpose only



## Specifications TLWMC15PBK

### Electrical Specifications

Model No.	TLWMC15PBK
Power (W) $\pm 10\%$	15 W (DLC: 16.31 W)
Input Voltage (V)	AC100/277V, 50/60Hz
Efficacy	112.75 lm/W
Power Factor (PF)	0.89

### Photometric Specifications

CRI	78.6
CCT	5000 K
Beam angle	77.3°
Light Output	1 839 lm
Dimmable	0-10V

### Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Clear
Net Weight	
Product size (mm)	175 x 280 x 133 mm
Product size (inch)	$\pm 6 \frac{7}{8} \times 11 \times 5 \frac{1}{4}$ po
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

## Product Description:

1. DLC 4.0 Standard.
2. Die cast aluminum housing provides solid mounting to wall.
3. Photocell optional.
4. Save on electricity consumption compared to fluorescent lighting fixture.
5. Color: black.  
Other colors available on special request.
6. Warranty: 5 Years.
7. It could be fitted with sensor.

## Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.

Similar products	Color	W	Lumen
TLWM50HPBK	5000 K	50 W	6281.5 lm
TLWM90PBK	5000 K	90 W	11 642 lm
TLWME90HPBK	5000 K	90 W	11 531 lm