



## Specifications TLWMC20PBK

### Electrical Specifications

Model No.	TLWMC20PBK
DLC ID	PK7LVTIR
Power (W) $\pm 10\%$	20 W (DLC: 19.7 W)
Input Voltage (V)	AC100/277V, 50/60Hz
Efficacy $\pm 3\%$	133.51 lm/W
Power Factor (PF)	0.887
Surge protection	N/A
Total harmonic distortion	$\leq 15\%$

### Photometric Specifications

CRI	84
CCT	5 000 K
Beam angle	77.3°
Light Output $\pm 3\%$	2 630.2 lm
Dimmable	0-10V

### Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Clear
Net Weight	2.5 kg
Product size (mm)	175 x 280 x 133 mm
Product size (inch)	$\pm 6 \frac{7}{8} \times 11 \times 5 \frac{1}{4}$ po
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

## Product Description:

- Die cast aluminum housing provides solid mounting to wall.
- Photocell optional.
- Save on electricity consumption compared to fluorescent lighting fixture.
- Color: black.  
Other colors available on special request.
- Warranty: 5 Years.
- It could be fitted with sensor.

## Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.