



Picture for illustration purpose only



## Specifications TLWME100PBK

### Electrical Specifications

Model No.	TLWME100PBK
Power (W) $\pm 10\%$	100 W (DLC: 99.41 W)
Input Voltage (V)	AC100/277V, 50/60Hz
Efficacy	121.94 lm/W
Power Factor (PF)	0.92

### Photometric Specifications

CRI	77.9
CCT	5000 K
Beam angle	104.9°
Light Output	12 122 lm
Dimmable	0-10V

### Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Clear
Net Weight	14.5 kg
Product size (mm)	362 x 235 x 203.5 mm
Product size (inch)	$\pm 14\text{-}1/4 \times 9\text{-}1/4 \times 8\text{po}$
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

## Product Description:

1. DLC 4.0 Standard.
2. Die cast aluminum housing provides solid mounting to wall.
3. Photocell optional.
4. Save on electricity consumption compared to fluorescent lighting fixture.
5. Color: black.  
Other colors available on special request.
6. Warranty: 5 Years.
7. It could be fitted with sensor.

## Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.

Similar products	Color	W	Lumen
TLWME100HPBK	5000 K	100 W	11 968 lm
TLWME140PBK	5000 K	140 W	17 149 lm
TLWM90PBK	5000 K	90 W	11 642 lm

[info@technilight.ca](mailto:info@technilight.ca)

**WWW.TECHNILIGHT.CA**