



Picture for illustration purpose only



Specifications TLWME140PBK

Electrical Specifications

Model No.	TLWME140PBK
Power (W) $\pm 10\%$	140 W (DLC: 140.7 W)
Input Voltage (V)	AC100/277V, 50/60Hz
Efficacy	121.88 lm/W
Power Factor (PF)	0.9

Photometric Specifications

CRI	76.3
CCT	5000 K
Beam angle	105.6°
Light Output	17 149 lm
Dimmable	0-10V

Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Clear
Net Weight	14.5 kg
Product size (mm)	462.2 x 230.6 x 228.6 mm
Product size (inch)	$\pm 18\text{-}1/4 \times 9\text{-}1/8 \times 9\text{-}0$
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

Product Description:

1. DLC 4.0 Standard.
2. Die cast aluminum housing provides solid mounting to wall.
3. Photocell optional.
4. Save on electricity consumption compared to fluorescent lighting fixture.
5. Color: black.
Other colors available on special request.
6. Warranty: 5 Years.
7. It could be fitted with sensor.

Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.

Similar products	Color	W	Lumen
TLWME140HPBK	5000 K	140 W	17 303 lm
TLWME100PBK	5000 K	100 W	12 122 lm
TLWM90PBK	5000 K	90 W	11 642 lm

info@technilight.ca

WWW.TECHNILIGHT.CA