



Picture for illustration purpose only



## Specifications TLWMF80PBK

### Electrical Specifications

Model No.	TLWMF80PBK
Power (W) $\pm 10\%$	80 W (DLC: 79.98 W)
Input Voltage (V)	AC100/277V, 50/60Hz
Efficacy	126.97 lm/W
Power Factor (PF)	0.9022

### Photometric Specifications

CRI	75.7
CCT	5000 K
Beam angle	111.7°
Light Output	10 155 lm
Dimmable	0-10V

### Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Clear
Net Weight	14.5 kg
Product size (mm)	307 x 200 x 207 mm
Product size (inch)	$\pm 12 \times 7\frac{7}{8} \times 8$ po
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

## Product Description:

1. DLC Premium.
2. Die cast aluminum housing provides solid mounting to wall.
3. Photocell optional.
4. Save on electricity consumption compared to fluorescent lighting fixture.
5. Color: black.  
Other colors available on special request.
6. Warranty: 5 Years.
7. It could be fitted with sensor.

## Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.

Similar products	Color	W	Lumen
TLWMF40PBK	5000 K	40 W	5 448 lm
TLWMF35HPBK	5000 K	35 W	4 374 lm
TLWMF70HPBK	5000 K	70 W	8 953.9 lm