



Adjustable CCT



Specifications TLWMU80ABK

Electrical Specifications

Model No.	TLWMU80ABK
DLC ID	PLE7VJJLMUH1
Power (W) $\pm 10\%$	80 W (DLC: 81.28 W)
Input Voltage (V)	AC 120/347V, 50/60Hz
Efficacy $\pm 3\%$	139.53 lm/W
Power Factor (PF)	0.937
Surge protection	4 Kv
Total harmonic distortion	<15%

Photometric Specifications

CRI	72.1
CCT	3000K / 4000K / 5000K
Beam angle	120°
Light Output $\pm 3\%$	11 341.4 lm
Dimmable	0-10V

Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Glass
Net Weight	3.9 kg
Product size (mm)	$\pm 362 \times 238 \times 192$ mm
Product size (inch)	$\pm 14.25 \times 9.36 \times 7.56$ in
Operating Humidity	10% - 90%
Operating Temperature	-30°C ~ 45°C
Lifespan (L70)	60 000 hours

Product Description:

- Large supply voltage range 120-347V.
- 3000K / 4000K / 5000K adjustable CCT.
- Die cast aluminum housing provides solid mounting to wall.
- Optional photocell.
- Save on electricity consumption compared to fluorescent lighting fixture.
- Color: black.
- Warranty: 5 Years.
- It could be fit with sensor.

Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.